

Fire Alarm Cable

Part Number: 4306

Description 18 AWG 2 Solid Conductors with Jacket

Ratings FPLR/CL2R, FT4 Sunlight Resistant

Approvals UL Listed

Construction

Conductor Type 18 AWG Solid Bare Copper

Conductor Count 2

Insulation Colors Black, Red

Insulation Type Polypropylene

Insulation Thickness 0.006" nom.

Cable Lay Length 2.00"

Shielding N/A

Rip Cord Yes

Jacket Material PVC

Jacket Thickness 0.016" nom.

Overall Outer Diameter 0.144" nom.

Flame Rating UL 1666 (Riser), CSA C22.2 No. 2556 (FT4)

Print Legend HONEYWELL P/N 4306 2C18 E175105 (UL) FPLR OR CL2R FT4 SUN RES (RoHS) 75C W/O
#XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

Electrical & Environmental

Temperature -20°C to 75°C

Voltage 300V max.

Capacitance 22.8 pF/ft. nom.

Impedance 67 Ohms nom.

DC Resistance 6.52 Ohms/1000' at 20°C

RoHS Compliant Yes

Packaging & Colors

Standard Packaging 1000' or 500' Speed Box® Pull Box

Standard Color(s) Red

Other packaging and color options available at <http://www.honeywellcable.com>

Donde comprar:

Ing Panama S.A
comercial@ingpanama.com
www.ingpanama.com